

# IR LED150-A-50

Home | Security | Lighting | Infrared

IR LED150-A-50

LED Infrared Illuminator 850nm, 50° 200-240VAC,

36W, Twilight Switch

**Art-Nr. 71732**



## Main Features

**Spectral emission: 850nm / Beam angle: 50°**  
130 LEDs with narrow-band light emission  
Sensor controlled twilight switch w. IR cut filter  
Integral switching power supply with softstart  
Power supply: 200 to 240VAC, 50Hz  
Efficiency factor: 97% (cos Phi >0.9)

**Low self-heating / Vibration-resistant**  
**Extended temperature range components included**  
**Natural-coloured anodized aluminium casing**  
**Protection rating: IP66**  
**Option: fastening, wall and ceiling mount brackets**

## Specifications

<b>Lamp type</b>	LED
<b>Spectral emission</b>	850 nm
<b>Spectral half-value range</b>	80nm
<b>Angle of light source h</b>	50°
<b>Angle of light source v</b>	50°
<b>Scene coverage</b>	75 m
<b>Twilight switch</b>	yes, 50/130Lux (ON/OFF) sensor controlled. Permanent Illuminator function by sensor covering (adhesive tap supplied) or in case of sensor failure
<b>Temperature related switch-off</b>	At >60°C (system temperature). Automatic restart after falling below the limits
<b>Isolation strength</b>	Class I (leakage path =>4mm)
<b>Efficiency factor</b>	>97% (PSU), Cos Phi: >0,9
<b>Switch-on delay</b>	Softstart

# IR LED150-A-50

(Continuation Specifications)

Heating above ambient air temperature	Max. 35°C
Connection	2m Mains connection cable with open ends
Power supply unit	integrated
Protection rating	IP66
Mount	2x Threads M8 for wall kit fixing
Supply voltage	200 ~240VAC +/-10%, 50Hz
Power consumption	36watts
Temperature range (operation)	-30°C ~+50°C
Housing ventilation	Via air vent
Housing	Aluminium with plastic cover
Colour	Housing: anodized silver / Black cover
Dimensions (HxWxD)	see drawing
Weight	1.9kg

## Optional accessories

71725	LED-WBSET	Wall Mount Set: Mounting Bracket and Wall Mount Bracket
71722	PM-80	Pole Mount Adapter IR LED-WBSET (80-180mm Pole)

# IR LED150-A-50


## Product information

\*) The best result will be achieved on condition that a camera is used with good sensitivity in the infra-red range, a relative lens aperture of F1.4 min. and a mean reflectance factor for spotlight objects.

# IR LED150-A-50

Home | Security | Lighting | Infrared

## Technical drawing



SLD Security & Communications  
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England  
Phone +44.1483225633 · Fax +44.1483225634  
sales@sld.co.uk · www.sld.co.uk

