

MDE-600-FW

600TVL, 3.6mm Fixed Lens, 12pc IR Leds



CAMERA FEATURES

- Day and night selection
- Auto white balance
- Armoured housing
- Colour/ Mono
- Discrete size
- Dual ring design
- Internal/External

SPECIFICATION

Image Sensor	1/3" Digital Sensor 1089
	CMOS
Horizontal Resolution	600TVL
Effective Pixels	PAL:752 (H) X 582 (V), NTSC:768 (H) X 494 (V)
Auto Electronic Shutter	PAL:1/50-1/100,000S, NTSC:1/60-1/100,000S
Sync.System	Internal
Lens	3.6mm Fixed Lens
Scanning System	2:1 Interlace
IR LED	12 PCS LED
IR Distance	10 M
S/N Ratio	≥48dB (AGC OFF)
Min Illumination	0 Lux (IR ON)
Auto Gain Control	Built in
White Balance	AUTO
Video output	1Vp-p, 75Ω
Gamma Correction	0.45
Power Supply	DC12V±10%
Current Consumption	50mA (IR OFF) ,120mA (IR ON)
IP Rating	IP66
Storage Temperature	-20°+60°
Operating Temperature	-10°+50°
Dimensions	Φ59x57mm
Weight	210g