

SC-17



A cost-effective 17" surveillance display with the quality, connectivity and performance essential for any security environment.

With the AG Neovo SC-17, security centres can keep an eye on budgets without losing sight of performance. Digital and analogue video inputs, including looping BNC I/O, minimise installation cost. Auto NTSC/PAL detection, settings key lock and auto settings adjustment reduce maintenance hassle. Quick signal-switching and rapid response time improve surveillance efficiency, while built-in speakers provide an additional level of security. All this and more make the SC-17 the perfect value display choice for any security environment.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-17

Specifications		SC-17
Panel	Panel Type	TFT LCD
	Panel Size	17.0" (433 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	250 cd/m ² (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	160°/160° (Typical)
	Display Colour	16.7M
	Response Time	3 ms (GTG)
Frequency (H/V)		H: 31 kHz - 80 kHz V: 50 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue	D-Sub via DVI-VGA cable
	Digital	29-Pin DVI-I
	BNC Security	BNC Connector in / out
Audio	Audio In	3.5 mm Audio Line-in
	Speaker	1W x 2
Power	AC-DC Adaptor	External
	Power	AC 100-240 V, 50-60 Hz
	Consumption	< 26 W (On) < 1.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	-5° ~ +15°
Dimensions	Product (W x H x D)	372 x 360 x 164mm (14.6" x 14.2" x 6.5")
	Packaging (W x H x D)	424 x 441 x 164mm (16.7" x 17.4" x 6.5")
Weight	Product Weight	3.6 kg (7.9 lbs)
	Packaged Weight	3.8 kg (8.4 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, CB, FCC, CE, BSMI, WEEE, RoHS
Accessories	Supplied	CD ROM (user manual and drivers), power cord, power adaptor, 29-Pin DVI-I cable, DVI-VGA cable, CVBS BNC connector cable



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI and BNC In/Out

SLD Security & Communications
 The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
 Phone +44.1483225633 · Fax +44.1483225634
 sales@sld.co.uk · www.sld.co.uk