

VAM-2

Home | Security | Processing | Accessories

VAM-2

Video/Audio HF-Modulator,

AV Signal Converting into UHF, 12VDC/230VAC

Art-Nr. 72686



Main Features

Video and Audio Signals to TV Set, or TV Networks
Adjustable Channel Range: 21 to 69
Antenna Loop-thru Input

Integrated Test Pattern Generator
Upto 3 Units Cascadable
Supply Voltage: 8-15VDC (PSU supplied)

Specifications

Weight	65g
Number of cascadable units	3 max.
UHF output level	70dBuV (-38dBm)
External adjustments	Test pattern ON/OFF, Channel selector +/-
Channel range	UHF: 21 ~69
LCD display	2-digit channel display
Temperature range	0°C ~+50°C
Test pattern generator	ON/OFF switchable
Video input	1Vp-p, 75ohms, Cinch
Audio input	500 mVeff +/-100mV, >10 kohms, Cinch
Transmission range	47 ~862MHz
Connectors	Video and Audio input: Cinch Antenna In/Out: RF, Power input
Supply voltage	8 ~12VDC
Housing	Aluminium, Light grey
Dimensions (HxWxD)	54x54x48mm
Parts supplied	Power supply unit 100 ~240VAC / 12VDC, 50/60Hz,; Manual

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

