

VDA-8CA

Home | Security | Processing | Distributors/Amplifiers

VDA-8CA
Video Signal Distributor 1-4 Inputs 2-8 Outputs,
Configurable, 230VAC

Art-Nr. 75102



Main Features

1 to 4 Inputs
2 to 8 Outputs
Video Bandwidth: 10MHz (+/-3db)
Signal-to-noise Ratio: >55db

Integrated Signal Pre-Amplification (Linear Gain)
Supply Voltage: 230VAC / 50Hz
Colour: Pantone Cool Gray 1C

Specifications

Video standard	PAL/NTSC
Video inputs	Up to 4x 1.0 ~2.0Vp-p, (C)VBS, 75ohms, BNC
Video outputs	2 ~8x 1.0 - 2.0Vp-p (C)VBS, 75Ohms, BNC
Distribution configurations	4x 1in/2out 2x 1in/4out 1in/6out and 1in/2out 1in/8out
Video signal bandwidth	0 ~10MHz (+/-3db)
Tilt	≤ 1% at 50Hz
Internal adjustments	4 jumper/channel for the output to the input configuration 1 Potentiometer/channel for the stepless adjustment of the linear gain
Signal-to-noise ratio	55dB
Signal pre-amplification range (linear gain)	-6db ~+6db stepless adjustable (separate per channel)
Temperature range	0°C ~+50°C
Supply voltage	230VAC/50Hz
Power consumption	6watts
Housing	Steel metal
Colour	Pantone Cool Gray 1C

VDA-8CA

(Continuation Specifications)

Dimensions (HxWxD)	44x216x240mm
Weight	2.5kg

Optional accessories

76407	VDA/AVU-RMK1	19" Rack Mount Kit for 1xVDA-8CA and AVU-8/2AL-2
76408	VDA/AVU-RMK2	19" Rack Mount Kit for 2xVDA-8CA and AVU-8/2AL-2

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

