

POE370U-480-8

Home | Security | IP Cameras | Accessories

POE370U-480-8
PoE Midspan, 8 Ports, 15.4W, Gigabit,
0° to +40°C, 100-240VAC

Art-Nr. 170048



SLD Security &
Communications

Main Features

Compliant with the IEEE802.3af standard	USB port for diagnostics and manual port control
Overload protection as per 802.3af specifications	Cisco Legacy detection
Transient voltage and over temperature protection	Full power of 125W (15.4W per port)
Overcurrent and short circuit protection	Voice-over-IP, Access point, Security application
Gigabit compatible (10/100/1000Base-T)	19" rack mounting kit included
Diagnostic LEDs	NIC Network Interface Card (optional)

Specifications

Switch type	PoE midspan
Ports	8
Power/port	15,4W
Remote control	no
Voltage input	100 - 240VAC
Output voltage	n/a
PoE standard	PoE (IEEE802.3af)
Cisco Legacy	yes
Gigabit	yes
Resistive power discovery	yes
Local Control	USB
Temperature range (operation)	0°C ~+40°C
19" Rack mountable	yes

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

