

POE576U-8AT

Home | Security | IP Cameras | Accessories

POE576U-8AT
PoE Midspan, 8 Ports, 33.6W, Gigabit, NIC, USB,
0° to +40°C, 100-240VAC

Art-Nr. 170056



SLD Security &
Communications

Main Features

Compliant with the IEEE802.3at standard	NIC Network Interface Card
Transient voltage and over temperature protection	Full power of 269W (33.6W per port)
Overcurrent and short circuit protection	GUI Graphical User Interface
Gigabit compatible (10/100/1000Base-T)	Cisco Legacy detection
Diagnostic LEDs	Voice-over-IP, Access point, Security application
USB port for diagnostics and manual port control	19" rack mounting kit included

Specifications

Switch type	PoE midspan
Ports	8
Power/port	33,6W
Remote control	no
Voltage input	100 - 240VAC
Output voltage	n/a
PoE standard	PoE+ (IEEE802.3at)
Cisco Legacy	yes
Gigabit	yes
Resistive power discovery	yes
Local Control	USB
Temperature range (operation)	0°C ~+40°C
19" Rack mountable	yes

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

